

DT. DL3091

Astra

PRODUCT DESCRIPTION

Smallest dimensions, discreet with medium or narrow beam.

Great for step washing.

For more information, please refer to [Astra Datasheet](#)



Construction	Die-cast aluminium, Stainless steel 316S (marine grade)
Colour (RAL finish)	Any custom RAL, Brushed stainless steel, Plated versions
Light source	3w LED (225lms) 700mA 4.5v DC
Colour temp.	2400K (special order), 2700K, 3000K CRI 85
Macadam	2
Beam angle	12 deg, 24 deg
Controls	On/off, Mains dim, DALI, Casambi (blue-tooth control of each fixture), 0-10V
Optional accessories	Anti-glare 'half-shield', Etched glass
Dimensions (mm)	40 × 50
Cut out Dimension (mm)	44
Special Notes	Order separately Wire-in-series., Requires remote IP rated driver., Supplied with metal recess tube.

VARIATIONS

Description	Colour (RAL finish)	Light source	Colour temp.	Beam angle	Controls	Optional accessories
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	On/off	Anti-glare 'half-shield'
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	On/off	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	Mains dim	Anti-glare 'half-shield'
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	Mains dim	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	DALI	Anti-glare 'half-shield'
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	DALI	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	Casambi (blue-tooth control of each fixture)	Anti-glare 'half-shield'
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	Casambi (blue-tooth control of each fixture)	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	0-10V	Anti-glare 'half-shield'
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	0-10V	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	On/off	Anti-glare 'half-shield'

Description	Colour (RAL finish)	Light source	Colour temp.	Beam angle	Controls	Optional accessories
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	On/off	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	Mains dim	Anti-glare 'half-shield'
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	Mains dim	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	DALI	Anti-glare 'half-shield'
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	DALI	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	Casambi (blue-tooth control of each fixture)	Anti-glare 'half-shield'
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	Casambi (blue-tooth control of each fixture)	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	0-10V	Anti-glare 'half-shield'
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	0-10V	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	On/off	Anti-glare 'half-shield'
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	On/off	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	Mains dim	Anti-glare 'half-shield'
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	Mains dim	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	DALI	Anti-glare 'half-shield'

Description	Colour (RAL finish)	Light source	Colour temp.	Beam angle	Controls	Optional accessories
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	DALI	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	Casambi (blue-tooth control of each fixture)	Anti-glare 'half-shield'
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	Casambi (blue-tooth control of each fixture)	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	0-10V	Anti-glare 'half-shield'
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	0-10V	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	On/off	Anti-glare 'half-shield'
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	On/off	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	Mains dim	Anti-glare 'half-shield'
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	Mains dim	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	DALI	Anti-glare 'half-shield'
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	DALI	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	Casambi (blue-tooth control of each fixture)	Anti-glare 'half-shield'
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	Casambi (blue-tooth control of each fixture)	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	0-10V	Anti-glare 'half-shield'
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	0-10V	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	On/off	Anti-glare 'half-shield'

Description	Colour (RAL finish)	Light source	Colour temp.	Beam angle	Controls	Optional accessories
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	On/off	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	Mains dim	Anti-glare 'half-shield'
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	Mains dim	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	DALI	Anti-glare 'half-shield'
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	DALI	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	Casambi (blue-tooth control of each fixture)	Anti-glare 'half-shield'
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	Casambi (blue-tooth control of each fixture)	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	0-10V	Anti-glare 'half-shield'
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	0-10V	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	On/off	Anti-glare 'half-shield'
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	On/off	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	Mains dim	Anti-glare 'half-shield'
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	Mains dim	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	DALI	Anti-glare 'half-shield'
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	DALI	Etched glass
Any custom RAL	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	Casambi (blue-tooth control of each fixture)	Anti-glare 'half-shield'

Description	Colour (RAL finish)	Light source	Colour temp.	Beam angle	Controls	Optional accessories
	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	Casambi (blue-tooth control of each fixture)	Etched glass
	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	0-10V	Anti-glare 'half-shield'
	Any custom RAL	3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	0-10V	Etched glass
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	On/off	Anti-glare 'half-shield'
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	On/off	Etched glass
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	Mains dim	Anti-glare 'half-shield'
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	Mains dim	Etched glass
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	DALI	Anti-glare 'half-shield'
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	DALI	Etched glass
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	Casambi (blue-tooth control of each fixture)	Anti-glare 'half-shield'
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	Casambi (blue-tooth control of each fixture)	Etched glass
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	0-10V	Anti-glare 'half-shield'
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	0-10V	Etched glass

Description	Colour (RAL finish)	Light source	Colour temp.	Beam angle	Controls	Optional accessories
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	On/off	Anti-glare 'half-shield'
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	On/off	Etched glass
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	Mains dim	Anti-glare 'half-shield'
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	Mains dim	Etched glass
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	DALI	Anti-glare 'half-shield'
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	DALI	Etched glass
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	Casambi (blue-tooth control of each fixture)	Anti-glare 'half-shield'
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	Casambi (blue-tooth control of each fixture)	Etched glass
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	0-10V	Anti-glare 'half-shield'
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	0-10V	Etched glass
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	On/off	Anti-glare 'half-shield'
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	On/off	Etched glass
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	Mains dim	Anti-glare 'half-shield'
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	Mains dim	Etched glass

Description	Colour (RAL finish)	Light source	Colour temp.	Beam angle	Controls	Optional accessories
Brushed stainless steel	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	DALI	Anti-glare 'half-shield'
Brushed stainless steel	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	DALI	Etched glass
Brushed stainless steel	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	Casambi (blue-tooth control of each fixture)	Anti-glare 'half-shield'
Brushed stainless steel	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	Casambi (blue-tooth control of each fixture)	Etched glass
Brushed stainless steel	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	0-10V	Anti-glare 'half-shield'
Brushed stainless steel	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	0-10V	Etched glass
Brushed stainless steel	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	On/off	Anti-glare 'half-shield'
Brushed stainless steel	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	On/off	Etched glass
Brushed stainless steel	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	Mains dim	Anti-glare 'half-shield'
Brushed stainless steel	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	Mains dim	Etched glass
Brushed stainless steel	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	DALI	Anti-glare 'half-shield'
Brushed stainless steel	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	DALI	Etched glass
Brushed stainless steel	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	Casambi (blue-tooth control of each fixture)	Anti-glare 'half-shield'
Brushed stainless steel	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	Casambi (blue-tooth control of each fixture)	Etched glass
Brushed stainless steel	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	0-10V	Anti-glare 'half-shield'
Brushed stainless steel	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	0-10V	Etched glass

Description	Colour (RAL finish)	Light source	Colour temp.	Beam angle	Controls	Optional accessories
Brushed stainless steel		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	On/off	Anti-glare 'half-shield'
Brushed stainless steel		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	On/off	Etched glass
Brushed stainless steel		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	Mains dim	Anti-glare 'half-shield'
Brushed stainless steel		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	Mains dim	Etched glass
Brushed stainless steel		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	DALI	Anti-glare 'half-shield'
Brushed stainless steel		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	DALI	Etched glass
Brushed stainless steel		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	Casambi (blue-tooth control of each fixture)	Anti-glare 'half-shield'
Brushed stainless steel		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	Casambi (blue-tooth control of each fixture)	Etched glass
Brushed stainless steel		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	0-10V	Anti-glare 'half-shield'
Brushed stainless steel		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	0-10V	Etched glass
Brushed stainless steel		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	On/off	Anti-glare 'half-shield'
Brushed stainless steel		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	On/off	Etched glass
Brushed stainless steel		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	Mains dim	Anti-glare 'half-shield'
Brushed stainless steel		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	Mains dim	Etched glass
Brushed stainless steel		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	DALI	Anti-glare 'half-shield'
Brushed stainless steel		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	DALI	Etched glass
Brushed stainless steel		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	Casambi (blue-tooth control of each fixture)	Anti-glare 'half-shield'

Description	Colour (RAL finish)	Light source	Colour temp.	Beam angle	Controls	Optional accessories
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	Casambi (blue-tooth control of each fixture)	Etched glass
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	0-10V	Anti-glare 'half-shield'
	Brushed stainless steel	3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	0-10V	Etched glass
	Plated versions	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	On/off	Anti-glare 'half-shield'
	Plated versions	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	On/off	Etched glass
	Plated versions	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	Mains dim	Anti-glare 'half-shield'
	Plated versions	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	Mains dim	Etched glass
	Plated versions	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	DALI	Anti-glare 'half-shield'
	Plated versions	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	DALI	Etched glass
	Plated versions	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	Casambi (blue-tooth control of each fixture)	Anti-glare 'half-shield'
	Plated versions	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	Casambi (blue-tooth control of each fixture)	Etched glass
	Plated versions	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	0-10V	Anti-glare 'half-shield'
	Plated versions	3w LED (225lms) 700mA 4.5v DC	2400K (special order)	12 deg	0-10V	Etched glass

Description	Colour (RAL finish)	Light source	Colour temp.	Beam angle	Controls	Optional accessories
Plated versions		3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	On/off	Anti-glare 'half-shield'
Plated versions		3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	On/off	Etched glass
Plated versions		3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	Mains dim	Anti-glare 'half-shield'
Plated versions		3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	Mains dim	Etched glass
Plated versions		3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	DALI	Anti-glare 'half-shield'
Plated versions		3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	DALI	Etched glass
Plated versions		3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	Casambi (blue-tooth control of each fixture)	Anti-glare 'half-shield'
Plated versions		3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	Casambi (blue-tooth control of each fixture)	Etched glass
Plated versions		3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	0-10V	Anti-glare 'half-shield'
Plated versions		3w LED (225lms) 700mA 4.5v DC	2400K (special order)	24 deg	0-10V	Etched glass
Plated versions		3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	On/off	Anti-glare 'half-shield'
Plated versions		3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	On/off	Etched glass
Plated versions		3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	Mains dim	Anti-glare 'half-shield'
Plated versions		3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	Mains dim	Etched glass

Description	Colour (RAL finish)	Light source	Colour temp.	Beam angle	Controls	Optional accessories
Plated versions		3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	DALI	Anti-glare 'half-shield'
Plated versions		3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	DALI	Etched glass
Plated versions		3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	Casambi (blue-tooth control of each fixture)	Anti-glare 'half-shield'
Plated versions		3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	Casambi (blue-tooth control of each fixture)	Etched glass
Plated versions		3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	0-10V	Anti-glare 'half-shield'
Plated versions		3w LED (225lms) 700mA 4.5v DC	2700K	12 deg	0-10V	Etched glass
Plated versions		3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	On/off	Anti-glare 'half-shield'
Plated versions		3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	On/off	Etched glass
Plated versions		3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	Mains dim	Anti-glare 'half-shield'
Plated versions		3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	Mains dim	Etched glass
Plated versions		3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	DALI	Anti-glare 'half-shield'
Plated versions		3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	DALI	Etched glass
Plated versions		3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	Casambi (blue-tooth control of each fixture)	Anti-glare 'half-shield'
Plated versions		3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	Casambi (blue-tooth control of each fixture)	Etched glass
Plated versions		3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	0-10V	Anti-glare 'half-shield'
Plated versions		3w LED (225lms) 700mA 4.5v DC	2700K	24 deg	0-10V	Etched glass

Description	Colour (RAL finish)	Light source	Colour temp.	Beam angle	Controls	Optional accessories
Plated versions		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	On/off	Anti-glare 'half-shield'
Plated versions		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	On/off	Etched glass
Plated versions		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	Mains dim	Anti-glare 'half-shield'
Plated versions		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	Mains dim	Etched glass
Plated versions		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	DALI	Anti-glare 'half-shield'
Plated versions		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	DALI	Etched glass
Plated versions		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	Casambi (blue-tooth control of each fixture)	Anti-glare 'half-shield'
Plated versions		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	Casambi (blue-tooth control of each fixture)	Etched glass
Plated versions		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	0-10V	Anti-glare 'half-shield'
Plated versions		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	12 deg	0-10V	Etched glass
Plated versions		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	On/off	Anti-glare 'half-shield'
Plated versions		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	On/off	Etched glass
Plated versions		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	Mains dim	Anti-glare 'half-shield'
Plated versions		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	Mains dim	Etched glass
Plated versions		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	DALI	Anti-glare 'half-shield'
Plated versions		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	DALI	Etched glass
Plated versions		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	Casambi (blue-tooth control of each fixture)	Anti-glare 'half-shield'

Description	Colour (RAL finish)	Light source	Colour temp.	Beam angle	Controls	Optional accessories
Plated versions		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	Casambi (blue-tooth control of each fixture)	Etched glass
Plated versions		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	0-10V	Anti-glare 'half-shield'
Plated versions		3w LED (225lms) 700mA 4.5v DC	3000K CRI 85	24 deg	0-10V	Etched glass

PRODUCT DESCRIPTION

Smallest dimensions, discreet with medium or narrow beam.

Great for step washing.

For more information, please refer to [Astra Datasheet](#)

