

DT. BS2045-marker

Cleo Marker IP67

PRODUCT DESCRIPTION

In-ground robust marker light fixed. Dimmable, IP rated. Low glare.

Great for pathway & orientation lighting in all external locations.



Construction	Die Cast Aluminium / Steel 316
Colour (RAL finish)	Brushed stainless steel, Plated versions
Light source	7w GU10 LED (545 lms) 240v
Colour temp.	2700K, 3000K, 4000K, CRI 90
Beam angle	n/a
Macadam	3
Controls	Mains dim, Casambi (allows individual control of each fixture)
Cut out Dimension (mm)	64mm (66mm with sleeve), 63 mm (65mm with sleeve)
Optional accessories	n/a
Special Notes	Choose one-aperture or two-aperture cover

VARIATIONS

Description	Colour (RAL finish)	Light source	Colour temp.	Beam angle	Controls	Optional accessories
	Brushed stainless steel	7w GU10 LED (545 lms) 240v	2700K	Any Beam angle	Mains dim	n/a
	Brushed stainless steel	7w GU10 LED (545 lms) 240v	2700K	Any Beam angle	Casambi (allows individual control of each fixture)	n/a
	Brushed stainless steel	7w GU10 LED (545 lms) 240v	3000K	Any Beam angle	Mains dim	n/a
	Brushed stainless steel	7w GU10 LED (545 lms) 240v	3000K	Any Beam angle	Casambi (allows individual control of each fixture)	n/a
	Brushed stainless steel	7w GU10 LED (545 lms) 240v	4000K	Any Beam angle	Mains dim	n/a
	Brushed stainless steel	7w GU10 LED (545 lms) 240v	4000K	Any Beam angle	Casambi (allows individual control of each fixture)	n/a
	Brushed stainless steel	7w GU10 LED (545 lms) 240v	CRI 90	Any Beam angle	Mains dim	n/a
	Brushed stainless steel	7w GU10 LED (545 lms) 240v	CRI 90	Any Beam angle	Casambi (allows individual control of each fixture)	n/a
	Plated versions	7w GU10 LED (545 lms) 240v	2700K	Any Beam angle	Mains dim	n/a
	Plated versions	7w GU10 LED (545 lms) 240v	2700K	Any Beam angle	Casambi (allows individual control of each fixture)	n/a
	Plated versions	7w GU10 LED (545 lms) 240v	3000K	Any Beam angle	Mains dim	n/a
	Plated versions	7w GU10 LED (545 lms) 240v	3000K	Any Beam angle	Casambi (allows individual control of each fixture)	n/a
	Plated versions	7w GU10 LED (545 lms) 240v	4000K	Any Beam angle	Mains dim	n/a
	Plated versions	7w GU10 LED (545 lms) 240v	4000K	Any Beam angle	Casambi (allows individual control of each fixture)	n/a
	Plated versions	7w GU10 LED (545 lms) 240v	CRI 90	Any Beam angle	Mains dim	n/a



Description	Colour (RAL finish)	Light source	Colour temp.	Beam angle	Controls	Optional accessories
	Plated versions	7w GU10 LED (545 lms) 240v	CRI 90	Any Beam angle	Casambi (allows individual control of each fixture)	n/a
	Any Colour (RAL finish)	Any Light source	Any Colour temp.	Any Beam angle	Mains dim	n/a
	Any Colour (RAL finish)	Any Light source	Any Colour temp.	Any Beam angle	Casambi (allows individual control of each fixture)	n/a
	Any Colour (RAL finish)	Any Light source	Any Colour temp.	Any Beam angle	Mains dim	n/a
	Any Colour (RAL finish)	Any Light source	Any Colour temp.	Any Beam angle	Casambi (allows individual control of each fixture)	n/a
	Any Colour (RAL finish)	Any Light source	Any Colour temp.	Any Beam angle	Mains dim	n/a
	Any Colour (RAL finish)	Any Light source	Any Colour temp.	Any Beam angle	Casambi (allows individual control of each fixture)	n/a
	Any Colour (RAL finish)	Any Light source	Any Colour temp.	Any Beam angle	Mains dim	n/a
	Any Colour (RAL finish)	Any Light source	Any Colour temp.	Any Beam angle	Casambi (allows individual control of each fixture)	n/a
	Any Colour (RAL finish)	Any Light source	Any Colour temp.	Any Beam angle	Mains dim	n/a
	Any Colour (RAL finish)	Any Light source	Any Colour temp.	Any Beam angle	Casambi (allows individual control of each fixture)	n/a
	Any Colour (RAL finish)	Any Light source	Any Colour temp.	Any Beam angle	Mains dim	n/a
	Any Colour (RAL finish)	Any Light source	Any Colour temp.	Any Beam angle	Casambi (allows individual control of each fixture)	n/a
	Any Colour (RAL finish)	Any Light source	Any Colour temp.	Any Beam angle	Mains dim	n/a
	Any Colour (RAL finish)	Any Light source	Any Colour temp.	Any Beam angle	Casambi (allows individual control of each fixture)	n/a

Description	Colour (RAL finish)	Light source	Colour temp.	Beam angle	Controls	Optional accessories
	Any Colour (RAL finish)	Any Light source	Any Colour temp.	Any Beam angle	Mains dim	n/a
	Any Colour (RAL finish)	Any Light source	Any Colour temp.	Any Beam angle	Casambi (allows individual control of each fixture)	n/a

PRODUCT DESCRIPTION

In-ground robust marker light fixed. Dimmable, IP rated. Low glare.

Great for pathway & orientation lighting in all external locations.



Two direction (aperture)

