

DT. Volans Premium 24v  
(add suffix see below)

---

## Volans Premium 120 LEDS IP20 IP65

---

### PRODUCT DESCRIPTION

Robust 120 LEDs per metre, heavy substrate material, still provides a shadow-free image.

CRI90 calibrated. 24v DC dimmable.

For more information, please refer to [Volans Premium 120 LEDS Datasheet](#)

---



<b>Construction</b>	PVC / plastic mix; copper conductors 4oz
<b>Colour (RAL finish)</b>	Clear
<b>Light source</b>	(2835) 10w/m LED (800 lms/m) 24v DC, (2835) 15w/m LED (1150 lms/m) 24v DC, (2835) 5w/m LED (400 lms/m) 24v DC, (5050) 20w/m LED (2000 lms/m) 24v DC
<b>IP Rating</b>	IP20, IP65
<b>Colour temp.</b>	2400K* (to order), 2700K, 3000K, 4000K, 6000k* (to order)
<b>Macadam</b>	3
<b>Controls</b>	Mains dim, DALI, Casambi (blue-tooth control of each fixture), 0-10V
<b>Dimensions (mm)</b>	4 x 8

**Cut out Dimension (mm)** n/a

**Special Notes** 10mm pitch, Cutting centres 50mm

## VARIATIONS

Description	Colour (RAL finish)	Light source	IP Rating	Colour temp.	Controls
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP65	3000K	Casambi (blue-tooth control of each fixture)
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP65	3000K	0-10V
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP65	4000K	Mains dim
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP65	4000K	DALI
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP65	4000K	Casambi (blue-tooth control of each fixture)
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP65	4000K	0-10V
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP65	6000k* (to order)	Mains dim
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP65	6000k* (to order)	DALI
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP65	6000k* (to order)	Casambi (blue-tooth control of each fixture)
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP65	6000k* (to order)	0-10V
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	2400K* (to order)	Mains dim
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	2400K* (to order)	DALI

Description	Colour (RAL finish)	Light source	IP Rating	Colour temp.	Controls
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	2400K* (to order)	Casambi (blue-tooth control of each fixture)
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	2400K* (to order)	0-10V
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	2700K	Mains dim
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	2700K	DALI
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	2700K	Casambi (blue-tooth control of each fixture)
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	2700K	0-10V
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	3000K	Mains dim
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	3000K	DALI
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	3000K	Casambi (blue-tooth control of each fixture)
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	3000K	0-10V
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	4000K	Mains dim
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	4000K	DALI
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	4000K	Casambi (blue-tooth control of each fixture)
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	4000K	0-10V
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	6000k* (to order)	Mains dim
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	6000k* (to order)	DALI

Description	Colour (RAL finish)	Light source	IP Rating	Colour temp.	Controls
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	6000k* (to order)	Casambi (blue-tooth control of each fixture)
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	6000k* (to order)	0-10V
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP20	2400K* (to order)	Mains dim
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP20	2400K* (to order)	DALI
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP20	2400K* (to order)	Casambi (blue-tooth control of each fixture)
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP20	2400K* (to order)	0-10V
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP20	2700K	Mains dim
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP20	2700K	DALI
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP20	2700K	Casambi (blue-tooth control of each fixture)
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP20	2700K	0-10V
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP20	3000K	Mains dim
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP20	3000K	DALI
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP20	3000K	Casambi (blue-tooth control of each fixture)
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP20	3000K	0-10V
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP20	4000K	Mains dim
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP20	4000K	DALI

Description	Colour (RAL finish)	Light source	IP Rating	Colour temp.	Controls
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP20	4000K	Casambi (blue-tooth control of each fixture)
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP20	4000K	0-10V
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP20	6000k* (to order)	Mains dim
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP20	6000k* (to order)	DALI
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP20	6000k* (to order)	Casambi (blue-tooth control of each fixture)
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP20	6000k* (to order)	0-10V
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP65	2400K* (to order)	Mains dim
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP65	2400K* (to order)	DALI
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP65	2400K* (to order)	Casambi (blue-tooth control of each fixture)
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP65	2400K* (to order)	0-10V
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP65	2700K	Mains dim
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP65	2700K	DALI
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP65	2700K	Casambi (blue-tooth control of each fixture)
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP65	2700K	0-10V
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP65	3000K	Mains dim
Clear		(2835) 10w/m LED (800 lms/m) 24v DC	IP65	3000K	DALI

Description	Colour (RAL finish)	Light source	IP Rating	Colour temp.	Controls
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP20	3000K	Casambi (blue-tooth control of each fixture)
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP20	3000K	0-10V
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP20	4000K	Mains dim
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP20	4000K	DALI
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP20	4000K	Casambi (blue-tooth control of each fixture)
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP20	4000K	0-10V
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP20	6000k* (to order)	Mains dim
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP20	6000k* (to order)	DALI
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP20	6000k* (to order)	Casambi (blue-tooth control of each fixture)
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP20	6000k* (to order)	0-10V
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	2400K* (to order)	Mains dim
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	2400K* (to order)	DALI
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	2400K* (to order)	Casambi (blue-tooth control of each fixture)
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	2400K* (to order)	0-10V
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	2700K	Mains dim
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	2700K	DALI

Description	Colour (RAL finish)	Light source	IP Rating	Colour temp.	Controls
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	2700K	Casambi (blue-tooth control of each fixture)
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	2700K	0-10V
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	3000K	Mains dim
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	3000K	DALI
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	3000K	Casambi (blue-tooth control of each fixture)
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	3000K	0-10V
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	4000K	Mains dim
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	4000K	DALI
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	4000K	Casambi (blue-tooth control of each fixture)
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	4000K	0-10V
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	6000k* (to order)	Mains dim
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	6000k* (to order)	DALI
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	6000k* (to order)	Casambi (blue-tooth control of each fixture)
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	6000k* (to order)	0-10V
	Clear	(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	2400K* (to order)	Mains dim
	Clear	(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	2400K* (to order)	DALI

Description	Colour (RAL finish)	Light source	IP Rating	Colour temp.	Controls
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	2400K* (to order)	Casambi (blue-tooth control of each fixture)
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	2400K* (to order)	0-10V
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	2700K	Mains dim
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	2700K	DALI
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	2700K	Casambi (blue-tooth control of each fixture)
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	2700K	0-10V
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	3000K	Mains dim
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	3000K	DALI
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	3000K	Casambi (blue-tooth control of each fixture)
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	3000K	0-10V
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	4000K	Mains dim
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	4000K	DALI
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	4000K	Casambi (blue-tooth control of each fixture)
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	4000K	0-10V
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	6000k* (to order)	Mains dim
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	6000k* (to order)	DALI



Description	Colour (RAL finish)	Light source	IP Rating	Colour temp.	Controls
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	6000k* (to order)	Casambi (blue-tooth control of each fixture)
Clear		(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	6000k* (to order)	0-10V
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP20	2400K* (to order)	Mains dim
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP20	2400K* (to order)	DALI
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP20	2400K* (to order)	Casambi (blue-tooth control of each fixture)
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP20	2400K* (to order)	0-10V
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP20	2700K	Mains dim
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP20	2700K	DALI
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP20	2700K	Casambi (blue-tooth control of each fixture)
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP20	2700K	0-10V
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP20	3000K	Mains dim
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP20	3000K	DALI
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP20	3000K	Casambi (blue-tooth control of each fixture)
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP20	3000K	0-10V
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP20	4000K	Mains dim
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP20	4000K	DALI

Description	Colour (RAL finish)	Light source	IP Rating	Colour temp.	Controls
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP20	4000K	Casambi (blue-tooth control of each fixture)
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP20	4000K	0-10V
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP20	6000k* (to order)	Mains dim
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP20	6000k* (to order)	DALI
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP20	6000k* (to order)	Casambi (blue-tooth control of each fixture)
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP20	6000k* (to order)	0-10V
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	2400K* (to order)	Mains dim
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	2400K* (to order)	DALI
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	2400K* (to order)	Casambi (blue-tooth control of each fixture)
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	2400K* (to order)	0-10V
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	2700K	Mains dim
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	2700K	DALI
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	2700K	Casambi (blue-tooth control of each fixture)
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	2700K	0-10V
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	3000K	Mains dim
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	3000K	DALI

Description	Colour (RAL finish)	Light source	IP Rating	Colour temp.	Controls
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	3000K	Casambi (blue-tooth control of each fixture)
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	3000K	0-10V
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	4000K	Mains dim
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	4000K	DALI
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	4000K	Casambi (blue-tooth control of each fixture)
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	4000K	0-10V
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	6000k* (to order)	Mains dim
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	6000k* (to order)	DALI
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	6000k* (to order)	Casambi (blue-tooth control of each fixture)
Clear		(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	6000k* (to order)	0-10V
Clear		(2835) 5w/m LED (400 lms/m) 24v DC	IP20	2400K* (to order)	Mains dim
Clear		(2835) 5w/m LED (400 lms/m) 24v DC	IP20	2400K* (to order)	DALI
Clear		(2835) 5w/m LED (400 lms/m) 24v DC	IP20	2400K* (to order)	Casambi (blue-tooth control of each fixture)
Clear		(2835) 5w/m LED (400 lms/m) 24v DC	IP20	2400K* (to order)	0-10V
Clear		(2835) 5w/m LED (400 lms/m) 24v DC	IP20	2700K	Mains dim
Clear		(2835) 5w/m LED (400 lms/m) 24v DC	IP20	2700K	DALI

Description	Colour (RAL finish)	Light source	IP Rating	Colour temp.	Controls
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP20	2700K	Casambi (blue-tooth control of each fixture)
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP20	2700K	0-10V
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP20	3000K	Mains dim
	Clear	(2835) 5w/m LED (400 lms/m) 24v DC	IP20	3000K	DALI
	Any Colour (RAL finish)	(2835) 10w/m LED (800 lms/m) 24v DC	IP65	3000K	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(2835) 10w/m LED (800 lms/m) 24v DC	IP65	3000K	0-10V
	Any Colour (RAL finish)	(2835) 10w/m LED (800 lms/m) 24v DC	IP65	4000K	Mains dim
	Any Colour (RAL finish)	(2835) 10w/m LED (800 lms/m) 24v DC	IP65	4000K	DALI
	Any Colour (RAL finish)	(2835) 10w/m LED (800 lms/m) 24v DC	IP65	4000K	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(2835) 10w/m LED (800 lms/m) 24v DC	IP65	4000K	0-10V
	Any Colour (RAL finish)	(2835) 10w/m LED (800 lms/m) 24v DC	IP65	6000k* (to order)	Mains dim
	Any Colour (RAL finish)	(2835) 10w/m LED (800 lms/m) 24v DC	IP65	6000k* (to order)	DALI
	Any Colour (RAL finish)	(2835) 10w/m LED (800 lms/m) 24v DC	IP65	6000k* (to order)	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(2835) 10w/m LED (800 lms/m) 24v DC	IP65	6000k* (to order)	0-10V
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	2400K* (to order)	Mains dim
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	2400K* (to order)	DALI

Description	Colour (RAL finish)	Light source	IP Rating	Colour temp.	Controls
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	2400K* (to order)	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	2400K* (to order)	0-10V
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	2700K	Mains dim
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	2700K	DALI
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	2700K	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	2700K	0-10V
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	3000K	Mains dim
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	3000K	DALI
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	3000K	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	3000K	0-10V
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	4000K	Mains dim
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	4000K	DALI
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	4000K	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	4000K	0-10V
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	6000k* (to order)	Mains dim
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP65	6000k* (to order)	DALI

Description	Colour (RAL finish)	Light source	IP Rating	Colour temp.	Controls
	Any Colour (RAL finish)	(RAL 5050) 20w/m LED (2000 lms/m) 24v DC	IP65	6000k* (to order)	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(RAL 5050) 20w/m LED (2000 lms/m) 24v DC	IP65	6000k* (to order)	0-10V
	Any Colour (RAL finish)	(RAL 2835) 10w/m LED (800 lms/m) 24v DC	IP20	2400K* (to order)	Mains dim
	Any Colour (RAL finish)	(RAL 2835) 10w/m LED (800 lms/m) 24v DC	IP20	2400K* (to order)	DALI
	Any Colour (RAL finish)	(RAL 2835) 10w/m LED (800 lms/m) 24v DC	IP20	2400K* (to order)	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(RAL 2835) 10w/m LED (800 lms/m) 24v DC	IP20	2400K* (to order)	0-10V
	Any Colour (RAL finish)	(RAL 2835) 10w/m LED (800 lms/m) 24v DC	IP20	2700K	Mains dim
	Any Colour (RAL finish)	(RAL 2835) 10w/m LED (800 lms/m) 24v DC	IP20	2700K	DALI
	Any Colour (RAL finish)	(RAL 2835) 10w/m LED (800 lms/m) 24v DC	IP20	2700K	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(RAL 2835) 10w/m LED (800 lms/m) 24v DC	IP20	2700K	0-10V
	Any Colour (RAL finish)	(RAL 2835) 10w/m LED (800 lms/m) 24v DC	IP20	3000K	Mains dim
	Any Colour (RAL finish)	(RAL 2835) 10w/m LED (800 lms/m) 24v DC	IP20	3000K	DALI
	Any Colour (RAL finish)	(RAL 2835) 10w/m LED (800 lms/m) 24v DC	IP20	3000K	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(RAL 2835) 10w/m LED (800 lms/m) 24v DC	IP20	3000K	0-10V
	Any Colour (RAL finish)	(RAL 2835) 10w/m LED (800 lms/m) 24v DC	IP20	4000K	Mains dim
	Any Colour (RAL finish)	(RAL 2835) 10w/m LED (800 lms/m) 24v DC	IP20	4000K	DALI

Description	Colour (RAL finish)	Light source	IP Rating	Colour temp.	Controls
Any Colour (RAL finish)	(RAL 2835)	10w/m LED (800 lms/m)	IP20	4000K	Casambi (blue-tooth control of each fixture)
Any Colour (RAL finish)	(RAL 2835)	10w/m LED (800 lms/m)	IP20	4000K	0-10V
Any Colour (RAL finish)	(RAL 2835)	10w/m LED (800 lms/m)	IP20	6000k* (to order)	Mains dim
Any Colour (RAL finish)	(RAL 2835)	10w/m LED (800 lms/m)	IP20	6000k* (to order)	DALI
Any Colour (RAL finish)	(RAL 2835)	10w/m LED (800 lms/m)	IP20	6000k* (to order)	Casambi (blue-tooth control of each fixture)
Any Colour (RAL finish)	(RAL 2835)	10w/m LED (800 lms/m)	IP20	6000k* (to order)	0-10V
Any Colour (RAL finish)	(RAL 2835)	10w/m LED (800 lms/m)	IP65	2400K* (to order)	Mains dim
Any Colour (RAL finish)	(RAL 2835)	10w/m LED (800 lms/m)	IP65	2400K* (to order)	DALI
Any Colour (RAL finish)	(RAL 2835)	10w/m LED (800 lms/m)	IP65	2400K* (to order)	Casambi (blue-tooth control of each fixture)
Any Colour (RAL finish)	(RAL 2835)	10w/m LED (800 lms/m)	IP65	2400K* (to order)	0-10V
Any Colour (RAL finish)	(RAL 2835)	10w/m LED (800 lms/m)	IP65	2700K	Mains dim
Any Colour (RAL finish)	(RAL 2835)	10w/m LED (800 lms/m)	IP65	2700K	DALI
Any Colour (RAL finish)	(RAL 2835)	10w/m LED (800 lms/m)	IP65	2700K	Casambi (blue-tooth control of each fixture)
Any Colour (RAL finish)	(RAL 2835)	10w/m LED (800 lms/m)	IP65	2700K	0-10V
Any Colour (RAL finish)	(RAL 2835)	10w/m LED (800 lms/m)	IP65	3000K	Mains dim
Any Colour (RAL finish)	(RAL 2835)	10w/m LED (800 lms/m)	IP65	3000K	DALI

Description	Colour (RAL finish)	Light source	IP Rating	Colour temp.	Controls
	Any Colour (RAL finish)	(RAL 2835) 5w/m LED (400 lms/m) 24v DC	IP20	3000K	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(RAL 2835) 5w/m LED (400 lms/m) 24v DC	IP20	3000K	0-10V
	Any Colour (RAL finish)	(RAL 2835) 5w/m LED (400 lms/m) 24v DC	IP20	4000K	Mains dim
	Any Colour (RAL finish)	(RAL 2835) 5w/m LED (400 lms/m) 24v DC	IP20	4000K	DALI
	Any Colour (RAL finish)	(RAL 2835) 5w/m LED (400 lms/m) 24v DC	IP20	4000K	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(RAL 2835) 5w/m LED (400 lms/m) 24v DC	IP20	4000K	0-10V
	Any Colour (RAL finish)	(RAL 2835) 5w/m LED (400 lms/m) 24v DC	IP20	6000k* (to order)	Mains dim
	Any Colour (RAL finish)	(RAL 2835) 5w/m LED (400 lms/m) 24v DC	IP20	6000k* (to order)	DALI
	Any Colour (RAL finish)	(RAL 2835) 5w/m LED (400 lms/m) 24v DC	IP20	6000k* (to order)	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(RAL 2835) 5w/m LED (400 lms/m) 24v DC	IP20	6000k* (to order)	0-10V
	Any Colour (RAL finish)	(RAL 2835) 5w/m LED (400 lms/m) 24v DC	IP65	2400K* (to order)	Mains dim
	Any Colour (RAL finish)	(RAL 2835) 5w/m LED (400 lms/m) 24v DC	IP65	2400K* (to order)	DALI
	Any Colour (RAL finish)	(RAL 2835) 5w/m LED (400 lms/m) 24v DC	IP65	2400K* (to order)	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(RAL 2835) 5w/m LED (400 lms/m) 24v DC	IP65	2400K* (to order)	0-10V
	Any Colour (RAL finish)	(RAL 2835) 5w/m LED (400 lms/m) 24v DC	IP65	2700K	Mains dim
	Any Colour (RAL finish)	(RAL 2835) 5w/m LED (400 lms/m) 24v DC	IP65	2700K	DALI



Description	Colour (RAL finish)	Light source	IP Rating	Colour temp.	Controls
	Any Colour (RAL finish)	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	2700K	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	2700K	0-10V
	Any Colour (RAL finish)	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	3000K	Mains dim
	Any Colour (RAL finish)	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	3000K	DALI
	Any Colour (RAL finish)	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	3000K	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	3000K	0-10V
	Any Colour (RAL finish)	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	4000K	Mains dim
	Any Colour (RAL finish)	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	4000K	DALI
	Any Colour (RAL finish)	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	4000K	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	4000K	0-10V
	Any Colour (RAL finish)	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	6000k* (to order)	Mains dim
	Any Colour (RAL finish)	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	6000k* (to order)	DALI
	Any Colour (RAL finish)	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	6000k* (to order)	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(2835) 5w/m LED (400 lms/m) 24v DC	IP65	6000k* (to order)	0-10V
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	2400K* (to order)	Mains dim
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	2400K* (to order)	DALI

Description	Colour (RAL finish)	Light source	IP Rating	Colour temp.	Controls
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	2400K* (to order)	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	2400K* (to order)	0-10V
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	2700K	Mains dim
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	2700K	DALI
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	2700K	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	2700K	0-10V
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	3000K	Mains dim
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	3000K	DALI
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	3000K	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	3000K	0-10V
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	4000K	Mains dim
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	4000K	DALI
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	4000K	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	4000K	0-10V
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	6000k* (to order)	Mains dim
	Any Colour (RAL finish)	(5050) 20w/m LED (2000 lms/m) 24v DC	IP20	6000k* (to order)	DALI

Description	Colour (RAL finish)	Light source	IP Rating	Colour temp.	Controls
	Any Colour (RAL (5050) finish)	20w/m LED (2000 lms/m) 24v DC	IP20	6000k* (to order)	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL (5050) finish)	20w/m LED (2000 lms/m) 24v DC	IP20	6000k* (to order)	0-10V
	Any Colour (RAL (2835) finish)	15w/m LED (1150 lms/m) 24v DC	IP20	2400K* (to order)	Mains dim
	Any Colour (RAL (2835) finish)	15w/m LED (1150 lms/m) 24v DC	IP20	2400K* (to order)	DALI
	Any Colour (RAL (2835) finish)	15w/m LED (1150 lms/m) 24v DC	IP20	2400K* (to order)	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL (2835) finish)	15w/m LED (1150 lms/m) 24v DC	IP20	2400K* (to order)	0-10V
	Any Colour (RAL (2835) finish)	15w/m LED (1150 lms/m) 24v DC	IP20	2700K	Mains dim
	Any Colour (RAL (2835) finish)	15w/m LED (1150 lms/m) 24v DC	IP20	2700K	DALI
	Any Colour (RAL (2835) finish)	15w/m LED (1150 lms/m) 24v DC	IP20	2700K	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL (2835) finish)	15w/m LED (1150 lms/m) 24v DC	IP20	2700K	0-10V
	Any Colour (RAL (2835) finish)	15w/m LED (1150 lms/m) 24v DC	IP20	3000K	Mains dim
	Any Colour (RAL (2835) finish)	15w/m LED (1150 lms/m) 24v DC	IP20	3000K	DALI
	Any Colour (RAL (2835) finish)	15w/m LED (1150 lms/m) 24v DC	IP20	3000K	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL (2835) finish)	15w/m LED (1150 lms/m) 24v DC	IP20	3000K	0-10V
	Any Colour (RAL (2835) finish)	15w/m LED (1150 lms/m) 24v DC	IP20	4000K	Mains dim
	Any Colour (RAL (2835) finish)	15w/m LED (1150 lms/m) 24v DC	IP20	4000K	DALI

Description	Colour (RAL finish)	Light source	IP Rating	Colour temp.	Controls
	Any Colour (RAL finish)	(RAL 2835) 15w/m LED (1150 lms/m) 24v DC	IP20	4000K	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(RAL 2835) 15w/m LED (1150 lms/m) 24v DC	IP20	4000K	0-10V
	Any Colour (RAL finish)	(RAL 2835) 15w/m LED (1150 lms/m) 24v DC	IP20	6000k* (to order)	Mains dim
	Any Colour (RAL finish)	(RAL 2835) 15w/m LED (1150 lms/m) 24v DC	IP20	6000k* (to order)	DALI
	Any Colour (RAL finish)	(RAL 2835) 15w/m LED (1150 lms/m) 24v DC	IP20	6000k* (to order)	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(RAL 2835) 15w/m LED (1150 lms/m) 24v DC	IP20	6000k* (to order)	0-10V
	Any Colour (RAL finish)	(RAL 2835) 15w/m LED (1150 lms/m) 24v DC	IP65	2400K* (to order)	Mains dim
	Any Colour (RAL finish)	(RAL 2835) 15w/m LED (1150 lms/m) 24v DC	IP65	2400K* (to order)	DALI
	Any Colour (RAL finish)	(RAL 2835) 15w/m LED (1150 lms/m) 24v DC	IP65	2400K* (to order)	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(RAL 2835) 15w/m LED (1150 lms/m) 24v DC	IP65	2400K* (to order)	0-10V
	Any Colour (RAL finish)	(RAL 2835) 15w/m LED (1150 lms/m) 24v DC	IP65	2700K	Mains dim
	Any Colour (RAL finish)	(RAL 2835) 15w/m LED (1150 lms/m) 24v DC	IP65	2700K	DALI
	Any Colour (RAL finish)	(RAL 2835) 15w/m LED (1150 lms/m) 24v DC	IP65	2700K	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(RAL 2835) 15w/m LED (1150 lms/m) 24v DC	IP65	2700K	0-10V
	Any Colour (RAL finish)	(RAL 2835) 15w/m LED (1150 lms/m) 24v DC	IP65	3000K	Mains dim
	Any Colour (RAL finish)	(RAL 2835) 15w/m LED (1150 lms/m) 24v DC	IP65	3000K	DALI

Description	Colour (RAL finish)	Light source	IP Rating	Colour temp.	Controls
	Any Colour (RAL finish)	(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	3000K	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	3000K	0-10V
	Any Colour (RAL finish)	(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	4000K	Mains dim
	Any Colour (RAL finish)	(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	4000K	DALI
	Any Colour (RAL finish)	(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	4000K	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	4000K	0-10V
	Any Colour (RAL finish)	(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	6000k* (to order)	Mains dim
	Any Colour (RAL finish)	(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	6000k* (to order)	DALI
	Any Colour (RAL finish)	(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	6000k* (to order)	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(2835) 15w/m LED (1150 lms/m) 24v DC	IP65	6000k* (to order)	0-10V
	Any Colour (RAL finish)	(2835) 5w/m LED (400 lms/m) 24v DC	IP20	2400K* (to order)	Mains dim
	Any Colour (RAL finish)	(2835) 5w/m LED (400 lms/m) 24v DC	IP20	2400K* (to order)	DALI
	Any Colour (RAL finish)	(2835) 5w/m LED (400 lms/m) 24v DC	IP20	2400K* (to order)	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	(2835) 5w/m LED (400 lms/m) 24v DC	IP20	2400K* (to order)	0-10V
	Any Colour (RAL finish)	(2835) 5w/m LED (400 lms/m) 24v DC	IP20	2700K	Mains dim
	Any Colour (RAL finish)	(2835) 5w/m LED (400 lms/m) 24v DC	IP20	2700K	DALI

Description	Colour (RAL finish)	Light source	IP Rating	Colour temp.	Controls
	Any Colour (RAL finish)	24v DC	IP20	2700K	Casambi (blue-tooth control of each fixture)
	Any Colour (RAL finish)	24v DC	IP20	2700K	0-10V
	Any Colour (RAL finish)	24v DC	IP20	3000K	Mains dim
	Any Colour (RAL finish)	24v DC	IP20	3000K	DALI

## PRODUCT DESCRIPTION

Robust 120 LEDs per metre, heavy substrate material, still provides a shadow-free image.

CRI90 calibrated. 24v DC dimmable.

For more information, please refer to [Volans Premium 120 LEDS Datasheet](#)

