

DT.Volans Premium COB Bass

VOLANS PREMIUM COB

PRODUCT DESCRIPTION

Linear flexible LED strip, 8mm wide with invisible Dow Corning resin coated IP20 / IP65 480 LEDs/M
UNIQUE COB LED of high quality CRI90. Totally dot-free and allows for 50mm cutting centres, fully dimmable.
Many profiles suitable for all general lighting applications.

For more information, please refer to [Volans Premium Cob iP20 datasheet](#)



Colour (RAL finish)	Clear
Light source	(COB) 10w/m LED (980 lms/m) 24v DC
Colour temp.	2400K (special order), 2700K, 3000K, 4000K, CRI 90+
Macadam	2
Controls	Mains dim, DALI, Casambi (blue-tooth control of each fixture), 0-10V
Dimensions (mm)	2 x 8
Cut out Dimension (mm)	n/a
Optional accessories	See data-sheet for driver selection & profiles

Special Notes Supplied with 1m attached 'power-lead'. Cutting and soldering service available. Supplied with 3m tape as standard. use with our range of profiles

VARIATIONS

Description	Colour (RAL finish)	Light source	Colour temp.	Controls	Optional accessories
Clear		(COB) 10w/m LED (980 lms/m) 24v DC	2400K (special order)	Mains dim	See data-sheet for driver selection & profiles
Clear		(COB) 10w/m LED (980 lms/m) 24v DC	2400K (special order)	DALI	See data-sheet for driver selection & profiles
Clear		(COB) 10w/m LED (980 lms/m) 24v DC	2400K (special order)	Casambi (blue-tooth control of each fixture)	See data-sheet for driver selection & profiles
Clear		(COB) 10w/m LED (980 lms/m) 24v DC	2400K (special order)	0-10V	See data-sheet for driver selection & profiles
Clear		(COB) 10w/m LED (980 lms/m) 24v DC	2700K	Mains dim	See data-sheet for driver selection & profiles
Clear		(COB) 10w/m LED (980 lms/m) 24v DC	2700K	DALI	See data-sheet for driver selection & profiles
Clear		(COB) 10w/m LED (980 lms/m) 24v DC	2700K	Casambi (blue-tooth control of each fixture)	See data-sheet for driver selection & profiles
Clear		(COB) 10w/m LED (980 lms/m) 24v DC	2700K	0-10V	See data-sheet for driver selection & profiles
Clear		(COB) 10w/m LED (980 lms/m) 24v DC	3000K	Mains dim	See data-sheet for driver selection & profiles
Clear		(COB) 10w/m LED (980 lms/m) 24v DC	3000K	DALI	See data-sheet for driver selection & profiles

Description	Colour (RAL finish)	Light source	Colour temp.	Controls	Optional accessories
Clear		(COB) 10w/m LED (980 lms/m) 24v DC	3000K	Casambi (blue-tooth control of each fixture)	See data-sheet for driver selection & profiles
Clear		(COB) 10w/m LED (980 lms/m) 24v DC	3000K	0-10V	See data-sheet for driver selection & profiles
Clear		(COB) 10w/m LED (980 lms/m) 24v DC	4000K	Mains dim	See data-sheet for driver selection & profiles
Clear		(COB) 10w/m LED (980 lms/m) 24v DC	4000K	DALI	See data-sheet for driver selection & profiles
Clear		(COB) 10w/m LED (980 lms/m) 24v DC	4000K	Casambi (blue-tooth control of each fixture)	See data-sheet for driver selection & profiles
Clear		(COB) 10w/m LED (980 lms/m) 24v DC	4000K	0-10V	See data-sheet for driver selection & profiles
Clear		(COB) 10w/m LED (980 lms/m) 24v DC	CRI 90+	Mains dim	See data-sheet for driver selection & profiles
Clear		(COB) 10w/m LED (980 lms/m) 24v DC	CRI 90+	DALI	See data-sheet for driver selection & profiles
Clear		(COB) 10w/m LED (980 lms/m) 24v DC	CRI 90+	Casambi (blue-tooth control of each fixture)	See data-sheet for driver selection & profiles
Clear		(COB) 10w/m LED (980 lms/m) 24v DC	CRI 90+	0-10V	See data-sheet for driver selection & profiles

PRODUCT DESCRIPTION

Linear flexible LED strip, 8mm wide with invisible Dow Corning resin coated IP20 / IP65 480 LEDs/M UNIQUE COB LED of high quality CRI90. Totally dot-free and allows for 50mm cutting centres, fully dimmable. Many profiles suitable for all general lighting applications.

For more information, please refer to [Volans Premium Cob iP20 datasheet](#)

Detail | lighting

